

Technical Data Sheet

Stripcure WB

Stripper for Hydrocarbon-based Curing Compounds

Description

Stripcure WB is a specifically formulated stripper for the removal hydrocarbon based curing compounds that are slow in oxidizing, due to the lack of UV or have been applied thickly to the concrete, creating an irregular patterns and high film build up.

Application

Before application ensure the surface to be treated is dry to eliminate dilution of Stripcure WB.

Apply Stripcure WB undiluted by brush, roller or spray to the surface to be treated. Allow the product to penetrate the surface of the concrete for 10 to 20 mins (depending on the thickness of the original film).

This material works by dissolving the hydrocarbon and does not allow the cure to reform.

Once emulsification has been achieved the surface can be pressure washed to remove the residue leaving the surface clean with no staining.

APPLICATION RATE:-

Sealing 5-10²m per litre (depending on thickness of the coating)

IT IS HIGHLY RECOMMENDED THAT APPLICATORS TEST ANY EVENRANGE SYSTEM BEFORE APPLICATION TO ENSURE COMPABILITY AS EACH SURFACE PROFILE VARIES WITH INDIVIDUAL CONDITIONS. PRODUCT IS COMBUSTABLE.

Available in 205lt & 20lt containers.

Typical Uses

- Precast Concrete
- Concrete Driveways
- Garage and Factory Floors
- Stencil and Slate Impression
- General Concrete Sealing

Features

- Suitable for sealing interior and exterior concrete surfaces
- Fair to good chemical and oil resistance
- Low odour, low toxicity, and non-flammable
- Rapid drying and reduced recoating downtime
- Excellent gloss retention

Contact

EVENRANGE PTY LTD
12 Frankston Gardens Drive
CARRUM DOWNS. Vic 3201 Aust
Phone 03 9782 3233
www.evenrange.com.au
ABN 92 062 754 545